

Installation Instructions:

Check and comply with local building codes.

DIRECTIONS FOR VENTING A RANGE HOOD OR MICROWAVE OVEN

Before starting, plan the installation and read all instructions.

If the range hood or microwave oven is equipped with a round exhaust outlet proceed to step 3.

If the range hood or microwave oven has a 3 ¼" x 10" exhaust outlet, start the installation by attaching the 3 ¼" x 10" to 7" round transition supplied to the rectangular outlet on the range hood or microwave oven.

Snap the lengths of pipe together and connect the non-crimped end of the first pipe to the round exhaust outlet or the transition previously installed. Continue connecting the lengths of pipe. From the attic, cut a 7 ½" round hole in the ceiling where the pipe will pass through to the roof. Note: Avoid beams and electrical connections.

Allow the pipe or adjustable elbow (if necessary) to extend through the previously cut hole in the roof. The pipe can be cut to the proper length from the non-crimped end to conform to the roof angle. Secure all pipe connections using supplied duct tape for a tight seal.

Refer to the additional instruction sheet to install the roof cap properly.

Secure the roof cap collar to the crimped end of the pipe using supplied duct tape.

Note: Check the range hood or microwave oven manufacturer's warranty for compliance.



Lambro Industries, Inc.
Amityville, NY 11701
www.lambro.net

Made in USA
Fabriqué aux États-Unis
Hecho en EE.UU.

