



**LAMBRO INDUSTRIES, INC.**

Ventilation Accessories Since 1967

## SEMI-RIGID

### UL 181 CLASS 0 AIR DUCT

Check with local building codes before installation.

**Product:** UL 181 Class 0 Air Duct

**Description:** The Double-Lock Aluminum ducting is an all-metal flexible duct constructed entirely without adhesive use. The Double-Lock mechanical joint makes an air-tight seam, while the circumferential corrugations provide excellent strength and flexibility. The minimum bend radius to the center line is one diameter. However, our recommended radius is 1 ½ diameters in accordance with accepted practice. Double-Lock Aluminum ducting can be easily cut to size and hand-formed.

**Construction:** A single-layer product made of aluminum is formed into a semi-rigid round flexible duct. The duct is labeled with the required UL marking.

**Components:**

- 1 layer of 0.0050-inch (thickness) aluminum

**Specifications:**

- Duct Diameter: 3-inch to 10-inch
- Plain ends

**Properties:**

Certified UL 181 Class 0 - Conforms to all requirements of UL 181 Class 0 Air Duct.

**Operating Temperature Range:** -60°F to +600°F

- Rated Velocity: 5,500 F.P.M.
- Internal Working Pressure (w.g.) 6" w.g. positive 6" w.g. negative
- Flame/Smoke: 0

**NOTE:** Per UL 181 Class 0 Air Ducts, no limitations to the installation length.

---

115 Albany Ave., Amityville, NY 11701  
(631) 842-8088  
sales@lambro.net  
www.lambro.net